



# Introducing **MAXXON**®

PRODUCTS LISTED AVAILABLE IN LOCAL INVENTORY

## CONCRETE FLOOR PREP SOLUTIONS



### UNGLUED

#### PRODUCT DESCRIPTION

Adhesive remover effective in the removal of pressure sensitive adhesives (PSAs) and other flooring mastics, glues and adhesives (water-based and non-water-based).

#### INFO

**Dry Time:** Typically 2-4 hours

**Coverage:** 80-100 ft<sup>2</sup>/gal

One kit covers 320-400 ft<sup>2</sup>

**Packaging:** 4 gal kit



### ISOLATE

#### PRODUCT DESCRIPTION

A two-part, water-based epoxy that isolates chemically-abated slabs, asbestos-containing material, and other contaminants in concrete slabs. Also prevents the migration of moisture vapor from adversely affecting floor coverings.

#### INFO

**Dry Time:** 4-6 hours

**Coverage:** 150 ft<sup>2</sup>/gal or 600 ft<sup>2</sup>/kit

**Packaging:** 4 gal bucket



### PROFILE

#### PRODUCT DESCRIPTION

Concrete cleaner and profiler designed to purge contaminants from concrete surface, while creating a CSP of 1-4 with no shotblasting. Biodegradable, clean with water.

#### INFO

**Dwell Time:** 15 min for surface cleaning

(approx) 2 hours to CSP 2

**Coverage:** 225-250 ft<sup>2</sup>/gal or 900-1,000 ft<sup>2</sup>/bucket

**Packaging:** 4 gal bucket

## PRIMERS



### FORTIFY™

#### PRODUCT DESCRIPTION

A high-performance primer to consolidate soft or dusty gypsum underlayments, strengthening and readying the surface for a Maxxon® underlayment.

#### INFO

**Packaging:** 5 gal bucket

**Total Coverage:** 400 ft<sup>2</sup> as consolidator



### GYPSUM OVERSPRAY

#### PRODUCT DESCRIPTION

Seals Maxxon underlayments before the installation of glue down finished floor goods.

#### INFO

**Packaging:** 5 gal bucket

**Total Coverage:** 10,500 ft<sup>2</sup>

“100% Employee Owned”...as employee owners, we take pride in serving you!

Copyright© 2023 Fishman Flooring Solutions. All rights reserved.

Toll Free 1-800-556-7899 customer.care@LFishman.com

## UNDERLAYMENTS & PATCH PRODUCTS



### LEVEL EZ™

#### PRODUCT DESCRIPTION

A low-prep, hydraulic cement-based underlayment that provides a strong, durable, smooth surface for floor coverings. Can be poured or pumped. UL Fire Rated.

#### INFO

**Installation Depth:** Featheredge to 2"

**Compressive Strength:** Minimum 5,000 psi

**Bag Size:** 50 lb

**Coverage** at 1/4": 21 ft<sup>2</sup>



### GYP-FIX EZ PATCH

#### PRODUCT DESCRIPTION

A high-strength, patch or skim coat over interior gypsum, concrete, and all subfloors. UL Fire Rated to maintain fire code.

#### INFO

**Compressive Strength:** Minimum 4,000 psi

**Bag Size:** 25 lb

**Coverage** at 1/8": 31 ft<sup>2</sup>



### EZ CRETE™

#### PRODUCT DESCRIPTION

A low-prep, cost-effective cementitious underlayment for leveling, smoothing and repairing interior gypsum and concrete subfloors. UL Fire Rated.

#### INFO

**Installation Depth:** 3/8" to 3"

**Compressive Strength:** Minimum 4,000 psi

**Bag Size:** 50 lb

**Coverage** at 3/8": 16 ft<sup>2</sup>

## CONCRETE REPAIR AND RENOVATION



### UNSET

#### PRODUCT DESCRIPTION

Thinset remover with advanced chemical de-bonding technology that is effective for the removal of many types of polymer-modified thinset and broadloom carpet adhesives. The easy to apply and fast-acting formula eliminates the need for mechanical removal of these products.

#### INFO

**Dwell Time:** Polymer modified thinsets - minimum 4 hours to overnight  
Broadloom carpets and adhesives - minimum 30 minutes to overnight

**Coverage:** Polymer

**Modified thinsets:** 80-120 ft<sup>2</sup>/gal (320-480 ft<sup>2</sup>/pail)

Broadloom carpets and adhesives: 50-100 ft<sup>2</sup>/gal (200-400 ft<sup>2</sup>/pail)

**Packaging:** 4 gal (15.1 L) of Unset in a 4.2 gal pail

**MAXXON**<sup>®</sup>  
COMMERCIAL

**SOLUTIONS FOR  
COMMERCIAL SUBFLOORS**

"100% Employee Owned"...as employee owners, we take pride in serving you!

Copyright© 2023 Fishman Flooring Solutions. All rights reserved.

Toll Free 1-800-556-7899 [customer.care@LFishman.com](mailto:customer.care@LFishman.com)