# **TAKE 5 | HIGH-MOISTURE SOLUTIONS**

## **FACE THE FACTS:**

Using the correct product and adhesive is crucial when installing floors on high-moisture concrete slabs. Failing to make the right selection may cause various issues in the flooring installation, including bubbling, curling, odor, debonding, and displacement.

Investing in the right solutions from the beginning not only ensures a successful installation but also prevents costly replacements and repairs.



### **DID YOU KNOW?**

Tarkett understands the need for solutions that may be used in high-moisture concrete environments. We offer a variety of full system flooring solutions and adhesive products to help you be successful with various levels of high moisture in concrete.

#### 959HM High-Moisture Adhesive

- Formulated to be used with the following LVT collections: iD Latitude™
- Moisture ASTM F2170: up to 99% RH on new concrete (95% on concrete 2+ years old)
- Purchase options: 4-gallon pail
- Application method: troweled
- Has a C2C Material Health Certificate<sup>™</sup> at the Bronze level.



## 100 Clear Thin Spread Adhesive

- Formulated to be used with all Tarkett VCT II products
- Moisture ASTM F2170: up to 95% RH
- Purchase options: 1-gallon or 4-gallon pail
- Application method: troweled
- Has a C2C Material Health Certificate<sup>™</sup> at the Platinum level.









#### RollSmart™

- Formulated to be used with Acczent<sup>™</sup>, Acczent
  Flourish<sup>™</sup>, Aria<sup>®</sup>, Melodia<sup>®</sup>, iQ<sup>®</sup> Optima<sup>®</sup>, iQ Granit, iQ
  Eminent, iQ Optima Acoustic, iQ Eminent Acoustic,
  Granit Safe.T homogeneous vinyl sheet; Contour,
  Event<sup>+</sup>, iD Latitude LVT, and MetalEdge
- Moisture ASTM F2170: up to 95% RH
- Purchase options: 1-gallon or 4-gallon pail
- Application method: rolled
- Has a C2C Material Health Certificate<sup>™</sup> at the Bronze level.





Please reach out to Technical Support or your local Tarkett business manager or sales representative with any questions.

Technical support:

Resilient: 800.899.8916 or resilient.technicalsupport@tarkett.com

