



Maxxon Corporation  
info@maxxon.com  
maxxon.com

920 Hamel Road  
P.O. Box 253  
Hamel, MN 55340

800.356.7887  
763.478.9600 OFF  
763.478.2431 FAX

December 11<sup>th</sup>, 2023

To Whom it May Concern,

I am writing to describe the performance and mechanism of Maxxon Commercial Unglued in the removal of a variety of flooring adhesives. Unglued contains both a liquid and solid component. The liquid component penetrates the adhesive swelling the polymers, loosening the bond to the floor, and making for easy removal. The solid component sits on the adhesive surface and helps with easy collection of the tacky polymer that is scraped loose of the floor.

Since the active component is absorbed into the adhesive itself the majority is removed with the scraped solids. Testing shows little absorption into the concrete surface. Scrubbing the floor surface with a black pad and closed loop water system will remove any traces. After scraping and wet scrubbing no significant Unglued will remain to interfere with curing or adhesion of new adhesive. Unlike other adhesive removers Unglued does not dissolve the adhesive being treated and so the adhesive does not penetrate further into the slab.

Please let me know if you have any further questions.

A handwritten signature in black ink, appearing to read "Erik Holmgren".

Erik Holmgren, Ph.D.  
VP of Research and Development  
Maxxon Corporation