



December 15, 2025

LOR #2025-348

Rob Hoffman
L Fishman
320 Outerbelt St.
Columbus, OH 43213

Project: Various Projects

Dear Mr. Hoffman,

In response to your request, MAPEI is pleased to state that Planiprep SC can be applied over a suitable, properly prepared concrete substate with RH readings up to 99% (ASTM F2170).

Planiprep SC is not a moisture barrier and will not block substate moisture from moving into the flooring installation system. The substrate moisture limits for the flooring installation system are dictated by the adhesive and flooring manufacturer's limits and will default to the lowest number that does not exceed 99% RH. The requirement of an under slab vapor retarder is based on the adhesive and flooring manufacturer's recommendations. Elevated substrate moisture and ambient conditions can affect the drying time of Planiprep SC. Additional drying time, up to seven days, may be required depending on the thickness of the application and conditions onsite.

Please follow all manufacturers' recommended installation procedures and industry standards to ensure a successful installation. Follow the flooring manufacturer's installation instructions and guidelines. MAPEI technical data sheets, material safety data sheets and surface preparation bulletins are available on our website www.mapei.com/US-EN.

Thank you for choosing MAPEI products. Please let us know if you have any questions.

Regards,

Logan Reavis

Logan Reavis
Technical Services Director

Tony Mancuso

Tony Mancuso
Sales Representative